



## Leisure Group Acrylic Steam Rooms

### STEAM ROOMS

#### Description+

Our range of steam rooms covers all popular sizes and configurations from a 2-person cabin to an 11-person steam room. They are assembled from pre-formed Acrylic panels mounted on an aluminium base frame.†

The internal Acrylic surface is resistant to the formation of bacteria and fungi, non-porous, smooth and easy to clean.†

The modular construction allows flexible planning and ease of assembly. Individual elements are manufactured from special grade white 8mm Acrylic with 8mm ABS reinforcement in the seating area to give added strength.†

The cabins have an anodised aluminium base frame to which the individual elements are screwed giving a finished structure that is rigid and very stable. The elements are connected with full length clamp strips over the external flanges with sealing gaskets between each joint.

The finished cabin is in shell form and will require insulation and cladding as necessary.†

The door is 8mm safety glass either clear or bronze tinted with a roller catch.†

Door position is as shown on the sectional plans and may be right or left hand hinged.†

Exact dimensions and a sketch plan of the required layout should be provided at the time of ordering.†

#### Requirements for Steam Cabin Installation+ (see separate sheet for more detailed information)

- 1) A suitable impervious floor surface with a level perimeter and fall (1:50) to a central drain must be provided before installation.†
- 2) Drain outlet with a diameter of 40mm.†
- 3) Ventilation to outside atmosphere with ducting to be connected to the ceiling of the steam cabin.†
- 4) Suitable electrical supply.†
- 5) Suitable site for steam generator with provision to allow free passage of steam from the pressure relief valve. The generator should be within 5 metres of the steam room.†
- 6) 1/2" mains water supply with stop-cock (at least 6ft head of pressure).†

#### Steam Rooms are supplied as follows:-

Acrylic wall and ceiling elements with flanges, sealing gaskets, joining clamps and fixing kit.†

Anodised aluminium base frame.†

Glass door with frame and handles.†

12v light fitting with transformer and 50w bulb.†

Steam generator with thermostatic controller and steam outlets with safety covers.

#### Prices

Model	Seats	Size in cms (w x d x h)	Steam Generator	Steam Outlets	
Type 2	4	210 x 110 x 210	4.7 kW	2	
Type 3 Corner	6	210 x 210 x 210	6 kW	2	
Type 4 / 1 to 2	6-7	210 x 210 x 210	6 kW	2	
Type 5 / 1 to 6	8-9	287 x 210 x 210	6 kW	3	
Type 5 corner	8-9	287 x 210 x 210	6 kW	3	
Type 6 / 1 to 5	10-11	364 x 210 x 210	9 kW	3	
Type 6 / Corner	10	364 x 210 x 210	9 kW	3	

Essence Dosing System £ 464

Aromatic Dosing System £575

We suggest for hard water areas that a water softener is used. See sales staff for details

Leisure Sales, Sunlight House, Calamine St, Macclesfield, 01625 501611 [www.leisuregroup.co.uk](http://www.leisuregroup.co.uk)